






TECHNICAL DATA SHEET - CST 0190/03 - 04/11/2013

PT 5504S

				
T	°C	-200 +280		
p	bar	500	150	
V	m/s	1	2	
pH		0 ÷ 14		



Avoid the product's use at the maximum temperature and pressure value associated without consult the manufacturer

Composition

PTFE multifilament yarns
Dispersion of PTFE

Features

This packing is braided with pure multifilament PTFE yarns impregnated with PTFE dispersion.

Applications

PT5504S can be used with all acid and basic fluids compatible with PTFE. Suitable to seal the industrial valves, reciprocating pumps and mixer slow motion. Suitable for food industry.

sezione mm	sezione inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	61,7	203	61,7	91,9
4,0	-	1,0	2,2	34,7	114	34,7	51,7
5,0	3/16	1,0	2,2	22,2	73	22,2	33,1
6,0	-	2,5	5,5	38,6	127	15,4	23,0
6,5	1/4	2,5	5,5	32,9	108	13,1	19,6
8,0	5/16	2,5	5,5	21,7	71	8,7	12,9
9,5	3/8	2,5	5,5	15,4	50	6,2	9,2
10,0	-	2,5	5,5	13,9	46	5,6	8,3
11,0	7/16	2,5	5,5	11,5	38	4,6	6,8
12,0	-	2,5	5,5	9,6	32	3,9	5,7
12,7	1/2	2,5	5,5	8,6	28	3,4	5,1
14,0	9/16	5,0	11,0	14,2	46	2,8	4,2
16,0	5/8	5,0	11,0	10,9	36	2,2	3,2
17,5	11/16	5,0	11,0	9,1	30	1,8	2,7
18,0	-	5,0	11,0	8,6	28	1,7	2,6
19,0	3/4	5,0	11,0	7,7	25	1,5	2,3
22,0	7/8	5,0	11,0	5,7	19	1,1	1,7
25,5	1	5,0	11,0	4,3	14	0,9	1,3

Packaged +/- 10 % in weight. Customized sizes and packaging are available on demand